



ISEKI SF237

OUTFRONT MOWER

35HP



ALL TORQUE. ALL ACTION.

ISEKI GIVES YOU THE EDGE



ISEKI SF237 SPECIFICATIONS

ENGINE		MOWER DECK SCMB60	
Type	Iseki E3FH	Type	Rotary rear discharge
Emissions regulations	Stage V	Cutting width	60"
No. of cylinders	3	No. of blades	2
Displacement	1.836	Adjustment	1 action lever
Output (hp)	35.4	Min cutting height	2mm
Fuel capacity	40 litres	MOWER DECK SCMBA54	
TRANSMISSION		Type	Rotary rear discharge
Type	Hydrostatic	Cutting width	54"
Forward	15 km/h	No. of blades	2
Reverse	10 km/h	Adjustment	1 action lever
4WD	Auto or 4WD	Min cutting height	25mm
BRAKES		MOWER DECK SSM54	
Type	Dry drum	Type	Rotary side discharge
TYRES		Cutting width	54"
Type	Turf	No. of blades	3
Front	23 x 10.50 - 12	Adjustment	Pin type
Rear	18 x 8.5 - 8	Min cutting height	25mm
DIMENSIONS		COLLECTOR SBC950	
Length	2,790mm	Capacity	950 litres
Wheelbase	1,325mm	Blower	Turbine fan
Height	1900mm	Dump & lift	Hydraulic
Weight	1,060kg	Dump height	2100mm



INTRODUCING THE NEW ISEKI SF237 OUT-FRONT MOWER COLLECTOR.

This model acts as the superseding model to the popular SF235 mower, offered with a powerful Stage V compliant 35 horsepower diesel engine. The SF range of out-front mowers are renowned for their flexibility and superior build quality, designed with a clear understanding of what commercial users want. With a choice of cutting decks measuring 54" or 60" wide, these high performance out-front mower-collectors are designed to facilitate grass cutting in the most difficult areas. Routine servicing and maintenance is refreshingly easy with excellent access to the engine, radiator and service points.



 **ISEKI**