



ISEKI SERIES

ISEKI SXG326

22HP



*Overseas model shown. Please confirm specification with your Iseki Dealer prior to purchase.

ALL TORQUE. ALL ACTION.

ISEKI GIVES YOU THE EDGE



ISEKI SXG326 SPECIFICATIONS

ENGINE	
Model	Iseki E3112
Number of cylinders	3
Displacement (L)	1.123
Output	22hp
Fuel tank capacity	21L
POWER TRAIN	
Transmission Type	Hydrostatic
Pedal type	2 pedals
Speeds:	Forward 0 – 17 km/h Reverse 0 – 10 km/h
Drive	2WD
MID PTO	
Type	Shaft drive
Speed	1750 rpm
Clutch	Belt tension
STEERING	
Type	Power steering
BRAKES	
Type	Power steering
Type	Internal expansion drum
Pedal type	1 pedal
Parking brake	Hook type
TYRE SIZE	
Turf Front	18 x 8.50 – 8
Turf Rear	26 x 10.50 – 12

DIMENSIONS	
Overall length	3250 mm
Overall width	1285 mm (without mower deck)
Overall height	1320 mm (with L-Dump)
Wheel base	1457 mm
Weight	796 kg
MOWER DECK	
Model	SCMA54
Cutting width	1372 mm
No. of blades	2 Synchronised Cutting Blades
Drive	Shaft
Cutting height	30 – 120 mm
Height of lift	150mm
Discharge	Centre
Blade overlap	60mm
Overall width	1440 mm
Overall height	385 mm
Overall length	945 mm
Weight	105 kg
GRASS COLLECTOR	
Overall width	1115 mm
Overall height	1440 mm
Overall length	1400 mm
Weight	138 kg
Container capacity	600L
Max discharge height	1940 mm
Lift & Dump system	Hydraulic



FULLY INTEGRATED HYDRAULIC CATCHER

- INCREASED CAPACITY OF 600L
- LARGE REAR DISCHARGE CHUTE



SPACIOUS OPERATOR'S AREA AND NEWLY DESIGNED EXTERIOR



EASY ENGINE ACCESS FOR SERVICEABILITY, LOW ENGINE NOISE

- 2 SYNCHRONISED CUTTING BLADES
- REAR PORTAL AXLE ALLOWS REAR DISCHARGE WITHOUT BLOWER
- CUTS AND DELIVERS IN ONE ACTION

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.

Part Number: MK001ISKXV01
Printed December 2022



www.iseki.com.au